

COPPER SB

GENERAL SPECIFICATIONS	
Charger	AC
Colour	Black
Connector type	Socket (Type 1 and Type 2)
Charging mode	Mode 3
Dimensions	260x192x113mm
Weight	2kg
Cable Length	-
Earthing Protection	-
ELECTRICAL SPECIFICATIONS	
Maximum Charging Power	7,4 kW (1Phase) / 22 kW (3Phase)
Rated Voltage AC \pm 10%	220 V to 240 V (7,4kW) 400 V (11kW and 22kW)
DC Voltage range	-
Rated Current	32 A (7,4 kW - 1Phase) 16 A (11 kW - 3Phase) 32 A (22 kW - 3Phase)
Cable Section	5x10mm ²
Configurable Current	from 6 A to rated current
Protection Rating	IP54 / IK08
Residual Current Detection	DC 6 mA
CONNECTIVITY & USER INTERFACE	
Connectivity	Wi-Fi / Ethernet / Bluetooth / Optional: 3G-4G
User Identification	RFID Card / myWallbox app
User Interface	myWallbox app & portal
Charger Status Information	RGB LED / myWallbox app & portal
Included Features	Power Sharing
Optional Features	Power Boost / Dynamic Power Sharing / MID Meter
Communication Protocol	myWallbox / OCPP 1.6j